



Hong Kong

3/F, Sun On Commercial Building,
112-114 Des Voeux Road C., Central, Hong Kong
Tel: (852) 2544 8580
Fax: (852) 2541 3903

Beijing

Unit 707, Office Tower C, Henderson Center,
18 Jian Guo Men Nei Avenue,
Dongcheng District, Beijing, China
Postal Code: 100005
Tel: (010) 6517 0082
Fax: (010) 6517 9570

Shanghai

Unit F112/F, Jian Jing Building,
1399 West Beijing Road,
Shanghai, China
Postal Code: 200040
Tel: (021) 6247 0333
Fax: (021) 6247 9980

Guangzhou

Unit A03-04, 8/F, East Block Yuexiu New Metropolis
Building, NO.232-238 Zhongshan 6th Road,
Guangzhou, China
Postal Code: 510180
Tel: (020) 3877 0618
Fax: (020) 3877 0228

Zhongshan

Zhong Shan Port, Zhong Shan City,
Guangdong, China
Sales Hotline: 400 628 9968

www.integrated.com



The ISO 9001 Certificate is valid for the Integrated operations at HK and Zhongshan.

ZimAccess series is the latest generation of access control system. It is an integral part of the Integrated Java Embedded Security System (JESS) which is designed based on Java EE architecture. The system offers you with reliable, secure and efficient access management solutions. The adoption of advanced ARM processor and CanBus communication protocol ensure high efficient data processing, high speed data transfer and data integrity. Its state-of-the-art single-piece enclosure design strengthens dust/waterproof ability of the reader; RFID-SIM module is embedded in the ZimAccess reader to support extended functions such as time attendance and point-of-sale using mobile phone. The sophisticated touch sensing keypad is designed for multi-factor authentication; and sharp LCD provides programmable Chi/Eng display. All these features make the ZimAccess series the best option for enterprises which are security demanding.

Controller Information

Characteristics

- Large and expandable memory size
200,000 cardholders
1 million in/out records, unlimited extensibility
- Prolonged data persistence
90 days' records storage
Guarantee data validity for 10 years without power
- High security
End-to-end security, advanced cryptographic technology, mutual-authentication between server software, controllers and readers
Encryption on all communication data
Password retry check
Two-factor authentication (card+password)
Duress code setting
Flexible card expiry date setting
Multi-zone anti-pass back function
VIP, blacklist card management
Multi-card access function, support max 256 cards per access point
- Various communication mode
Build-in TCP/IP function, CanBus communication function Support RS485, Wiegand communication
- Thunder/static electricity protection
- Low voltage check and auto shutdown protection

Time zone control

- 1 global time zone
- 256 group time zones
- 2,000 individual time zones
- Password time zone
- Emergency door status setting
- Alarm signal enable time zone
- Door release button time zone
- Electric lock control time zone
- Door open too long time zone

System Compatibility

- 1 controller can support 16 readers
- DHCP, Static IP

Power Supply & Backup Battery

- 220V AC power input
- Output: 18V AC, 7AH

Card Information

Mobile SIM Card (RFID-SIM)

- Mutual-authentication
- 2.4G Wireless technology
- Standard SIM card size

ID Card (HID)

- (000-255) 3 digits facility code
- +card number, Unique code is guaranteed
- 26bit standard Wiegand format
- Integrated standard format
- 125KHz

IC card (Mifare, HID iclass)

- (000-255) 3 digits facility code
- +card number, Unique code is guaranteed
- 13.56MHz

Software Characteristics

General Features

- Web base network version (multi-tier architecture)
- Central server management, cross platform operation
- Cross international time zone system configuration
- Real-time data upload (status/event/transactions), various encryption technology ensures data security
- Developed based on Java EE platform, system extensibility and scalability enhanced
- Online/offline mode
- Operation system: Windows, Linux, Unix
- Database: MS SQL Server / Oracle / MySQL
- Window base database application (Simplified / traditional Chinese, English)

Attendance Module

- Multiple time zone per day
- Cross locale holiday setting
- Unlimited shift table definition
- Unlimited roster table definition
- Reduce the risk of clock in fraud

Point-of-Sale

- POS online/offline mode, facilitate value-added service such as time attendance, billing statement, SMS notification of remaining balance

Access Control Report

- Entry record audit report
- Alarm status report
- System event report

Reporting

- Different kinds of reports
- Report output: printer or text file

Reader Information

ZA1 Dimensions (mm)

- Surface Mount
- 148(L) x 105(W) x 26(H)

Response Time

- Less than 0.1 second
- Mobile SIM: less than 0.5 second

Read Range

- Mifare: 3cm
- Mobile SIM: 4cm

* Maximum reading distance will vary according to installed environment.

* Owing to continuous product improvements, Product Technical and Aesthetic Specifications are subjected to change without further notice.



integrated